



**The award winning FlatMesh™ platform uses a wireless mesh-networked, intelligent sensor system consisting of small, easy to deploy devices, equipped with sensing, communication and computation capabilities.**

In a FlatMesh™ system the devices ‘talk’ to their neighbours, relaying data in a series of hops to the outside world. This dynamic, non-hierarchical system is extremely robust and can tolerate damage to individual devices without systematic loss of performance. It is suited to dense networks concentrated in relatively small areas. It is particularly appropriate for sites that are difficult to access, with obstructions that would constrain other technologies.

The FlatMesh™ platform incorporates a significant level of network intelligence, enabling not just a degree of self-configuration and self-healing, but responsiveness to events.

### **Features of Wireless Mesh Networking**

At a technical level, FlatMesh™ has been tested and proven over a decade of deployments in highly demanding environments, and prior to that, in five years of research at University College London, one of the world’s most respected engineering universities.

The proprietary communications protocol is based on the industry standard IEEE 802.15.4 PHY and MAC layers, operating in the global 2.4GHz ISM band. Deployed as part of an integrated system that can incorporate many sensor types, FlatMesh™ is ideal for complex applications such as construction sites or buildings where obstructions are common and accidental damage to parts of the wireless monitoring system is possible.

Nodes communicate to find the optimal route, transmitting data to the gateway in a series of “hops”. In the event of a sensor node or gateway dropping out for any reason the other nodes

will find an alternative route; this provides a significant level of robustness and redundancy. It also enables highly flexible deployment configurations, particularly in comparison to hub and spoke wireless alternatives.

Continuous improvement to sensor interface and wireless algorithms has resulted in ultra-low power consumption and very long battery life, with many sensor nodes capable of lasting up to 15 years while taking precision samples every 30 minutes and relaying messages through the mesh.

Gateways are pre-configured so the system will function as soon as it is installed. Users can choose from connection options including USB or RS232 connection to local equipment, or connectivity via an integrated solar powered cellular gateway. Alternatively, where mains power is available, the FlatMesh system can be connected directly to other databases, data loggers or industrial PCs.

The system is highly intelligent and enables remote users to interact with nodes and the gateway, for example to re-configure the frequency of readings. Data are transmitted to our user friendly WebMonitor software, or can be sent to many widely used third party data viewing platforms. To read more about Webmonitor, please visit <https://www.senceive.com/webmonitor>.

FlatMesh™ users benefit from many years of technical development and experience gained in a wide range of challenging applications. With tens of thousands of sensors around the world running on FlatMesh™ technology, you can be confident that you are using a reliable system built on quality, precision and durability.

## FlatMesh™ Specifications

Parameter	Value
Communication Type	Proprietary FlatMesh™ v3 Mesh Networking Protocols IEEE 802.15.4
Frequency Band	2400 – 2485 MHz ISM Band
Maximum Network Size	Up to 100 nodes. Wireless cameras can also be incorporated
Range between nodes, node to gateway	Up to 300 m

## Certifications

Approved for use in most countries. Sector-specific approvals in place for a number of industries, including rail.

To find out more about FlatMesh™, please visit

<https://www.senceive.com/flatmesh-geowan-platforms/flatmesh>

Get in touch today:

**1300 867 266**

[info@positionpartners.com.au](mailto:info@positionpartners.com.au)

[www.positionpartners.com.au](http://www.positionpartners.com.au)

Australia • New Zealand • SE Asia



*Shaping New Dimensions*